

Diesel Genset Specification

PL9D1

General technical data

Model	PL9D1	Rated voltage V	Current A
Structure	PT	220	40.9
Prime power (PRP): kVA / kW	9 / 9	230	39.1
Standby power (ESP): kVA / kW	10 / 10	240	37.5
Frequency: Hz	50		
Rotate speed: RPM	1500	Load	Fuel consumption L/h
Phase: P	1	25%	1.61
Power factor: cosφ	1.0	50%	2.54
Protection class	IP54	75%	3.12
Noise level: dB@7m	64.5	100%	3.55
Tank capacity: L	70	110%	N/A

Main Features

Design Standards	Environmental Operating Conditions	Factory Inspection
• Conformance Européenne (CE) • ISO8528-5:2005 • AS 3000-2018 • AS 3010-2017	• Installation place: outdoor / indoor (well ventilated). • Ambient temperature: -25°C to 45°C (the coolant heater is needed when the temperature is below 5°C) • Humidity: Less than 80% • Altitude: Below one thousand (1000) meters.	• Protection devices working test • Starting ability in normal temperature • 50% rated power load moment capacity • Load test :0, 25%, 50%, 75%, 100%, 110%

Power Class Definition

- Prime Power (PRP): the unit runs continuously with variable load, the number of operating hours is not limited, and 1h overload 10% operation is allowed per 12h, and the average load factor is less than 70% per 24h.
- Standby Power (ESP): operating time does not exceed 500h per year, continuous operating time does not exceed 300h, the average load factor is less than 80% per 24h. Overload operation is not allowed.

Product Statement

- The data of specifications is based on the following standard environmental test conditions.
 - Ambient temperature 25°C
 - Altitude 100m
 - Relative humidity 30%

Diesel Genset Specification

PL9D1

Power System

Engine

Manufacturer / brand	YangDong	Intake system	Natural aspirated
Model	YD385D	Intake resistance: kPa	≤3.0
Cylinders	3L	Exhaust back pressure: kPa	≤6.0
Bore: mm	85	Oil capacity: L	4.5
Stroke: mm	90	Coolant capacity: L	3.5
Displacement: L	1.532	Battery voltage: V	12
Compression ratio	18	Dimensions: mm	587×474×615
Rotate speed: RPM	1500	Dry weight: kg	175
Prime power: kWm	11.0		
Standby power: kWm	12.1		
Rotate speed governor	Mechanical		
Type of fuel Injection	Direct		

Alternator

Manufacturer / brand	POWERLINK	Insulation class	H
Model	PL1E-1	Temperature rising class	H
Exciter	Standard self-excitation, SHUNT	Protection class	IP23
Windings	100% copper	Voltage regulation	±0.5%
Winding pitch	2/3	Telephone harmonic factor THF	<2%
Number of poles	4	Telephone interference factor TIF	<50
Terminals	12		

Control System

Brand	COMAP		
Model	AMF5		
General Functions		Monitoring and protection	
– Automatic start / stop control		Oil pressure	Over load
– Manual/remote start control		Water temperature	Over current
– Real time monitoring and display of multiple parameters		Rotate speed	Over voltage
– CAN and Modbus communication		Start	Under voltage
– Provide complete control solutions		Running time	Over frequency
		Battery voltage	Under frequency
			

Diesel Genset Specification



PL9D1

Product Configuration

Engine	Generator	Control switchgear	Canopy (sound-proof)	Base Frame
Electrical start motor	Alternator	PLC control system	SECC Electrogalvanized sheet	Steel base frame
Battery system	H class insulation	Main circuit breaker	Corrosion-resistant coating	Engine bracket
Speed control system	H class temp. rising	Breaker cabinet	Access door	Alternator bracket
Lockable isolator switch	IP23 protection	ATS connector	Stainless steel hinge	Radiator bracket
Battery charger	AVR voltage regulator	Mains floating charger	Sound absorbing cotton	Vibration isolators

Fuel system	Lubrication system	Cooling system	Intake / exhaust system	Service documents
Base frame fuel tank	Oil pressure sensor	Radiator	Air filter	Installation and operation manual
Fuel level sensor	Oil temperature sensor	Water level sensor	Exhaust muffler	Test report
Flexible connection pipe	Oil filter	Water pipe	Exhaust bellow	Wiring diagram
Fuel filter	Manual oil drain pump		Exhaust pipe and flange	Warranty manual
	Oil drain ball valve		High temperature protective sleeve	Engine manual

Weight and Dimension



Dimension: L x W x H (mm)

1410x724x1128

Dry Weight (kg)

804

Note: Dimensions, weight and other parameters are for reference only, which shall be subject to the final design drawing.