



MODEL OVERVIEW	
SPEED	3000RPM
POWER	5kW / 6.5kVA
FUEL TYPE	DIESEL
FUEL CAPACITY	5.5L
CONTINUOUS OUTPUT	6.5kVA

ADDITIONAL INFO	
OUTLETS	1 x 10AMP 240V, 1 x 15AMP 240V SWITCHED WITH THERMAL OVERLOAD
FRAME	EXTRA LARGE ROLL FRAME
NOISE RATING	80 dBA @ 7M

TECHNICAL	
MODEL	GHD5000E
TYPE	PORTABLE
FREQUENCY	50Hz
PHASE/VOLTAGE	1/240

Hyundai Powered Heavy Duty Industrial Generators

Featuring a durable open-frame design and genuine Hyundai Engine, these generators are designed to provide maximum power output, making them perfect for heavy-duty applications. They deliver consistent and stable power to keep your tools, equipment, and appliances running smoothly. With unmatched durability and performance, these generators are built to handle even the toughest jobs.

Materials and specifications are subject to change. Specification sheets are current as of 30/6/2025.

FEATURES	
HYUNDAI DIESEL ENGINE	
HEAVY DUTY ROLL FRAME	
ELECTRIC START	
3 YEAR LIMITED ENGINE WARRANTY	

ENGINE	
MANUFACTURER	HYUNDAI
ENGINE MODEL	CP192FE
TYPE & CYLINDER	O.H.V. SINGLE CYLINDER
STARTING	ELECTRIC START
RUN TIME	3.6 HR @ 75% LOAD
CUBIC CAPACITY	406 CM ³
OIL CAPACITY	1.65 L

ALTERNATOR	
TYPE	AC SYNCHRONOUS BRUSHLESS
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

DIMENSIONS	
LENGTH	87 CM
WIDTH	60 CM
HEIGHT	77 CM
WEIGHT (DRY)	96 KG

OPTIONS	
HIRE SPEC: 2 x IP66 RATED OUTLETS, CIRCUIT BREAK and RCD PROTECTION	
2 OR 4 WHEEL KIT	

The warranty does not cover damage caused by misuse, neglect, accident, improper installation, unauthorised repairs or modifications, normal wear and tear, or use of non-approved fuels or oils. Consumable parts such as filters, fuses, and cosmetic wear are not covered.

The generator must be serviced at regular intervals as specified in the user manual. Proof of purchase and service records may be required. As the Australian distributor, Genelite reserves the right to repair or replace defective parts at its discretion.