



TECHNICAL OVERVIEW

MODEL	LG10K-1
PRIME POWER	10 kVA / 8 kW
STANDBY POWER	11 kVA / 8.8 kW
FUEL TYPE	DIESEL
SPEED	1500 RPM
TYPE	HEAVY DUTY
FREQUENCY	50Hz
PHASE/VOLTAGE	SINGLE PHASE / 240V
FUEL CAPACITY	105 LTR

ENGINE

MANUFACTURER	KUBOTA
ENGINE MODEL	D1105
CYLINDER/ CAPACITY	3 CYL / 1.123 LTR
INDUCTION	NATURALLY ASPIRATED
FUEL CONSUMPTION	3.5 L/HR @ 100% LOAD 2.9 L/HR @ 75% LOAD 1.8 L/HR @ 50% LOAD
GOVERNOR	MECHANICAL
OIL CAPACITY	5.1 LTR
COOLANT CAPACITY	6.4 LTR

FEATURES

SILENCED CANOPY – 67 dB(A) @ 7M
HOT DIPPED GALVANISED SKID BASE WITH FORK POCKETS
BUNDED FUEL TANK – 36 HOUR RUN TIME @ 75% LOAD
CANOPY – GALVANISED POWDER COAT
BATTERY CHARGER AND ISOLATOR
OUTLETS – 3 x 15 AMP 240V

CONTROLS

BRAND AND MODEL	DEEPSEA 6120
CIRCUIT BREAKER	TWO POLE

ALTERNATOR

BRAND AND MODEL	STAMFORD SOL1-P1
TYPE	BRUSHLESS / AVR
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

OPTIONS

ADDITIONAL OUTLETS
MINE SPEC
JACKET WATER HEATER
EXTERNAL FUEL CONNECTION
AUTO TRANSFER SWITCHES (ATS)

DIMENSIONS

LENGTH / WIDTH / HEIGHT	203.8 CM / 85 CM / 115.5 CM
WEIGHT (DRY)	670 KG

PRIME POWER (PRP): Continuous operation at variable load unlimited hours per year, with an average load factor of 75%. 10% overload capability is 1 hour in a 12 hour period of operation.

STANDBY POWER RATING (ESP): Emergency power supply with an average load factor of 85%. No overload capability. Limited to 400 hours per year.

